

Steraffirm")

owie Dick Test Pack AIR REMOVAL

Life Sciences

The Steraffirm Bowie Dick Test Packs are preassembled single-use test packs designed to evaluate the performance of the air removal system of a pre-vacuum equipped sterilizer at 121°-124°C (250°-255°F). Each Steraffirm Bowie Dick Test pack consists of a series of steam penetration (air removal) barriers into which a chemical indicator sheet is embedded. During the pre-vacuum cycle, air must be removed or displaced from the barrier material and steam must replace the air throughout the pack. A uniform change from yellow to blue/purple indicates adequate steam penetration. The Steraffirm Bowie Dick Test Pack is manufactured in the absence of lead and other heavy metals.

Steraffirm[®] Bowie Dick Test Packs Air Removal Test for Steam Sterilizers

FEATURES	BENEFITS
Conforms to ISO 11140-4:2007 standards	Meets a critical standard as a Bowie Dick alternative indicator for the detection of steam penetration
Preassembled, single-use pack	Eliminates the need to construct test packs
Abrupt and distinctive total color change from yellow to blue/purple	Facilitates interpretation of test pack results
Test pack available for 121°-124°C/250°-255F	Designed for Life Science application conditions
Ink is free of lead	No concern over exposure to harmful metals
Indicators can be kept as permanent record	Valuable documentation of air removal efficacy

STERIS offers the industry's finest technical support in addition to the leading sterility assurance products. Our Technical Service Group's expertise comes from years of servicing and troubleshooting sterilization systems at our Customers' facilities worldwide. Industry leading products and unmatched technical service is the STERIS difference.

STERAFFIRM BOWIE DICK SPECIFICATIONS

PRODUCT	DESCRIPTION	QUANTITY
EQC003	Steraffirm Bowie Dick Test Packs for 121-124°C/250-255°F	20 test packs/box

OPERATING PARAMETERS

- 121°-124°C (250°-255°F) cycle temperature
- 8 to 8.3 minutes/cycle based on temperature setting

CYCLE TYPE

Pre-vacuum

STANDARD

• ISO 11140-4:2007

STORAGE CONDITIONS

• Store between 0°C-30°C (32°-86°F) at 30-60% relative humidity away from direct sunlight

SHELF LIFE

36 months from time of manufacture

RECOMMENDED FOR DAILY USE

<section-header>COLORS ARE AN APPROXIMATIONImage: Image: Image



STERIS CORPORATION 5960 Heisley Road Mentor, OH 44060, USA T +1 800 444 9009

www.STERISLifeSciences.com

STERIS Offices Worldwide

Asia Pacific	+65 (0) 68 41 7677
Canada	+1 800 444 9009
Finland	+358 9 25851
France	+33 (0) 2 38 84 85 40
Germany	+49 (0) 221 466120
Italy	+39 (0) 2 21303 424
Latin America	+1 800 444 9009
Spain	+34 (0) 916 585 920
United Kingdom	+44 (0) 1256 840400

STERIS Life Sciences | Science & Solutions for Life

For over 100 years, STERIS has been known as a global leader, trusted partner and solutions provider in the field of sterilization and contamination control. *Today,* STERIS continues building on this heritage by advancing the *Science* of sterilization, cleaning and infection control while offering *Solutions* that meet our Customers' needs and high standards. STERIS is dedicated to helping you enhance the *Life* of your patients and the life of your equipment. From Formulated Chemistries, to Capital Equipment, to Parts and Services, STERIS Life Sciences is *Science & Solutions for Life*.

© 2015 STERIS Corporation All rights reserved No part of this publication may be reproduced in any material form without the permission of STERIS Corp.